

Description

Thread Size: 1/4", Head Width: 1/4", KFN542 series nut

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | KFN5423 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5310-01-057-0889 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



P/N KFN542-3 Specifications

| | |
|---|---|
| Thread Class: | 3b |
| Thread Direction: | Right-hand |
| Locking Feature: | Prevailing Torque All Metal Design |
| Washer Outside Diameter: | 0.363 Inches Maximum |
| Counterbore Diameter: | 0.223 Inches Minimum Nut And 0.228 Inches Maximum Nut |
| Overall Height: | 0.243 Inches Maximum |
| Nut Style: | Flat With Turned Up Edge |
| Nut Counterbore Depth: | 0.097 Inches Maximum Nut |
| Width Across Flats: | 0.243 Inches Minimum And 0.251 Inches Maximum |
| Temp Rating: | 450.0 Deg Fahrenheit Maximum |
| Thread Series: | Unjf |
| Thread Quantity Per Inch: | 32 |
| Nominal Thread Size: | 0.190 Inches |
| Special Features: | Rockwell C Scale 40 Min And Rockwell C Scale 45 Max Washer |
| Material: | Steel Comp 4140 Nut Or Steel Comp 4340 Nut Or Steel Comp 8740 Nut |
| Material: | Steel Washer |
| Material Document And Classification: | Mil-s-5626 Mil Spec 1st Material Response Nut Or Mil-s-5000 Mil Spec 2nd Material Response Nut Or Mil-s-6049 Mil Spec 3rd Material Response Nut |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl2 Fed Spec All Treatment Responses Overall |

How to Order

Order this self-locking assembled washer nut from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+assembled+washer+nuts/KFN542-3 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.