

# P/N KFN600-08

## **Description**

six point, aluminum nut

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**


SKU / Model: KFN60008

Minimum Qty (MOQ): 25

NSN: 5310-01-069-2740

ECCN: EAR99

National Motor Freight: 093490, Bolt / Nut / Screw / Clips / Fastener / Etc









<sup>\*</sup> See page 2 for technical characteristics

# **P/N KFN600-08 Specifications**

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Washer Outside Diameter:	0.288 Inches Minimum And 0.292 Inches Maximum
Counterbore Diameter:	0.198 Inches Minimum Nut And 0.202 Inches Maximum Nut
Lubrication:	Dry Film Lubricant
Overall Height:	0.270 Inches Maximum
Nut Style:	Hexagon
Nut Counterbore Depth:	0.102 Inches Minimum Nut And 0.112 Inches Maximum Nut
Width Across Flats:	0.212 Inches Minimum And 0.220 Inches Maximum
Temp Rating:	212.0 Deg Fahrenheit Maximum
Thread Series:	Unjc
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.164 Inches
Special Features:	Dyed Red
Material:	Aluminum Alloy 7075 Overall
Material Document And Classification:	Qq-a-225/9,t73 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec Single Treatment Response Overall

### **How to Order**

Order this self-locking extended washer nut from our inventory online by visiting <a href="https://military-fasteners.com/nuts/self\_locking+extended+washer+nuts/KFN600-08">https://military-fasteners.com/nuts/self\_locking+extended+washer+nuts/KFN600-08</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.