

# P/N LC-C6

### **Description**

Use NAS1080-06

\* Manufacturer certifications are shipped with your order EREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: LCC6

Minimum Qty (MOQ): 100

NSN: 5320-01-046-7461

Schedule B: 7616.10.1000

ECCN: EAR99

National Motor Freight: 013120, Aluminum Article Noi Sub 6



<sup>\*</sup> See page 2 for technical characteristics

# **P/N LC-C6 Specifications**

Collar Outside Diameter:	0.317 Inches Minimum And 0.327 Inches Maximum
Collar Overall Height:	0.233 Inches Minimum And 0.263 Inches Maximum
Lubrication:	Cetyl Alcohol
Collar Inside Diameter:	0.187 Inches Minimum And 0.193 Inches Maximum
Collar Style:	Configural Type
Material:	Aluminum Alloy 2024 Overall
Material Document And Classification:	Ams 4120 Assn Std Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625,type 2 Mil Spec Single Treatment Response Overall

## **How to Order**

Order this collar from our inventory online by visiting <a href="https://military-fasteners.com/collars/collars/LC-C6">https://military-fasteners.com/collars/collars/LC-C6</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/collars/collars/LC-C6">https://military-fasteners.com/collars/collars/LC-C6</a> and selecting the quantity you want then click "add to cart".