

Description

Fastener Length: 4-13/32", Thread: 6-32, Thread Length: 19/64

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	LE11100322166
Minimum Qty (MOQ):	1
NSN:	5305-01-219-5933
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N LE111-0032-2166 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.252 Inches Minimum And 0.302 Inches Maximum
Fastener Length:	4.387 Inches Minimum And 4.417 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.244 Inches Minimum And 0.279 Inches Maximum
Internal Drive Style:	Torque Set
End Item Identification:	Aircraft, B-1b
Nominal Thread Diameter:	0.138 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum And 40.0 Rockwell C Maximum
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Steel Comp E4340 Or Steel Comp 4140 Or Steel Comp 8740 Or Steel Comp 8735 Or Steel Comp 6150
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-p-416,ty2,cl2 Fed Spec Single Treatment Response
Thread Series Designator:	Unjc

How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/LE111-0032-2166> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.