

Description

Fastener Length: 21/32", Thread: 8-32, Thread Length: 23/64

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | LE11100322205 |
| Minimum Qty (MOQ): | 1 |
| NSN: | 5305-01-218-3127 |
| Schedule B: | 7318.15.6080 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N LE111-0032-2205 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.314 Inches Minimum And 0.364 Inches Maximum |
| Fastener Length: | 0.636 Inches Minimum And 0.666 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.294 Inches Minimum And 0.332 Inches Maximum |
| Internal Drive Style: | Torque Set |
| Nominal Thread Diameter: | 0.164 Inches |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Hardness Rating: | 36.0 Rockwell C Minimum And 40.0 Rockwell C Maximum |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Screw Material: | Steel Comp E4340 Or Steel Comp 4140 Or Steel Comp 8740 Or Steel Comp 8735 Or Steel Comp 6150 |
| Screw Surface Treatment: | Cadmium And Chromate |
| Screw Surface Treatment Document And Classification: | Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response |
| Special Features: | Internal Drive Ribbed |
| Thread Series Designator: | Unjc |

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/LE111-0032-2205> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.