

P/N LE111-0032-2303

Description

SKII / Model:

Fastener Length: 17/32", Thread: 10-32, Thread Length: 23/64

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Sito / Modeli	2211100322303	
Minimum Qty (MOQ):	1	
NSN:	5305-01-184-7686	
Schedule B:	7318.15.6080	

LF11100322303

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N LE111-0032-2303 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.314 Inches Minimum And 0.364 Inches Maximum
Fastener Length:	0.512 Inches Minimum And 0.542 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.344 Inches Minimum And 0.385 Inches Maximum
Internal Drive Style:	Torque Set
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum And 40.0 Rockwell C Maximum
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Steel Comp E4340 Or Steel Comp 4140 Or Steel Comp 8740 Or Steel Comp 8735 Or Steel Comp 6150
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response
Special Features:	Internal Drive Ribbed
Thread Series Designator:	Unjf

How to Order

Order this machine screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/LE111-0032-2303 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outher to complete your order.