

P/N LE111-0041-2407

Description

Fastener Length: 7/8", Thread: 1/4-28, Thread Length: 7/16

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

| SKU / Model: | LE11100412407 |
|-------------------------|--------------------------------------|
| Minimum Qty (MOQ): | 1 |
| NSN: | 5305-01-214-5067 |
| Schedule B: | 7318.15.6080 |
| ECCN: | EAR99 |
| National Motor Freight: | 136500, Metal Noi / Metal Alloys Noi |



^{*} See page 2 for technical characteristics

P/N LE111-0041-2407 Specifications

| Thread Class: | 3a |
|---------------------------------------|--|
| Thread Direction: | Right-hand |
| Thread Length: | 0.400 Inches Minimum And 0.450 Inches Maximum |
| Fastener Length: | 0.848 Inches Minimum And 0.878 Inches Maximum |
| Head Style: | Oval Countersunk |
| Head Diameter: | 0.390 Inches Minimum And 0.395 Inches Maximum |
| Grip Diameter: | 0.2485 Inches Minimum And 0.2495 Inches Maximum |
| Internal Drive Style: | Offset Cruciform (torque Set) |
| Nominal Thread Diameter: | 0.250 Inches |
| Grip Length: | 0.438 Inches Nominal |
| Thread Quantity Per Inch: | 28 |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Surface Finish: | 32.0 Microinches Grip |
| Surface Finish: | 32.0 Microinches Threads |
| Special Features: | Internal Drive Ribbed |
| Material: | Titanium Alloy Overall |
| Material Document And Classification: | Ams 4967 Assn Std Single Material Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this machine screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/LE111-0041-2407 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outher to complete your order.