

Description

Fastener Length: 45/64", Thread: 6-32, Thread Length: 45/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	LE11200232111
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-263-3804
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N LE112-0023-2111 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.611 Inches Minimum And 0.703 Inches Maximum
Fastener Length:	0.673 Inches Minimum And 0.703 Inches Maximum
Head Style:	Pan No. 2
Head Diameter:	0.256 Inches Minimum And 0.270 Inches Maximum
Head Height:	0.087 Inches Minimum And 0.097 Inches Maximum
Internal Drive Style:	Torque Set
Nominal Thread Diameter:	0.138 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum And 40.0 Rockwell C Maximum
Screw Material:	Steel Comp E4340 Or Steel Comp 4140 Or Steel Comp 8740 Or Steel Comp 8735 Or Steel Comp 6150
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-p-416 Ty2 Cl2 Fed Spec Single Treatment Response
Special Features:	Internaldrive Ribbed
Thread Series Designator:	Unjc

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/LE112-0023-2111> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.