

P/N LE112-0025-2312

Description

Fastener Length: 3/4", Thread: 10-32, Thread Length: 3/4"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: LE11200252312

Minimum Qty (MOQ): 5 EA

NSN: 5305-01-272-4771

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 136500, Metal Noi / Metal Alloys Noi



^{*} See page 2 for technical characteristics

P/N LE112-0025-2312 Specifications

| Thread Class: | 3a |
|---|---|
| Thread Direction: | Right-hand |
| Thread Length: | 0.673 Inches Minimum And 0.765 Inches Maximum |
| Fastener Length: | 0.735 Inches Minimum And 0.765 Inches Maximum |
| Head Style: | Pan No. 2 |
| Head Diameter: | 0.360 Inches Minimum And 0.374 Inches Maximum |
| Head Height: | 0.115 Inches Minimum And 0.125 Inches Maximum |
| Internal Drive Style: | Torque Set |
| Nominal Thread Diameter: | 0.190 Inches |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Screw Material: | Titanium Alloy Uns R56400 |
| Screw Material Document And Classification: | Ams4967 Assn Std Single Material Response |
| Special Features: | Internal Drive Ribbed |
| Thread Series Designator: | Unjf |

How to Order

Order this screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/LE112-0025-2312 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/LE112-0025-2312 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/LE112-0025-2312 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/LE112-0025-2312 and selecting the quantity you want selection to the selection of the sel