

Description

Fastener Length: 1-3/16", lockbolt,

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	LGPL2SPV0604AC
Minimum Qty (MOQ):	10
NSN:	5320-01-329-4254
Schedule B:	8108.90.3060
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



P/N LGPL2SP-V06-04AC Specifications

Fastener Length:	1.000 Inches Minimum And 1.200 Inches Maximum
Head Style:	Err-090
Head Height:	0.047 Inches Minimum And 0.057 Inches Maximum
Shank Diameter:	0.1885 Inches Minimum And 0.1895 Inches Maximum
Shank Style:	Pin-rivet, Multiple Grooved
Head Major Diameter:	0.289 Inches Minimum And 0.299 Inches Maximum
Lubrication:	Cetyl Alcohol
Grip Length:	0.189 Inches Minimum And 0.250 Inches Maximum
Shear Strength:	95000 Single Pounds Per Square Inch
Material:	Titanium Alloy Uns R56400 Overall
Material Document And Classification:	Ams 4967 Assn Std Single Material Response Overall
Surface Treatment:	Aluminum Overall
Surface Treatment Document And Classification:	Nas 4006 Assn Std Single Treatment Response Overall

How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/LGPL2SP-V06-04AC> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.