

**Description**

Fastener Length: 1-3/16", lockbolt,

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	LGPL2SPV0604AC
Minimum Qty (MOQ):	10
NSN:	5320-01-329-4254
Schedule B:	8108.90.3060
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



## P/N LGPL2SP-V06-04AC Specifications

<b>Fastener Length:</b>	1.000 Inches Minimum And 1.200 Inches Maximum
<b>Head Style:</b>	Err-090
<b>Head Height:</b>	0.047 Inches Minimum And 0.057 Inches Maximum
<b>Shank Diameter:</b>	0.1885 Inches Minimum And 0.1895 Inches Maximum
<b>Shank Style:</b>	Pin-rivet, Multiple Grooved
<b>Head Major Diameter:</b>	0.289 Inches Minimum And 0.299 Inches Maximum
<b>Lubrication:</b>	Cetyl Alcohol
<b>Grip Length:</b>	0.189 Inches Minimum And 0.250 Inches Maximum
<b>Shear Strength:</b>	95000 Single Pounds Per Square Inch
<b>Material:</b>	Titanium Alloy Uns R56400 Overall
<b>Material Document And Classification:</b>	Ams 4967 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Aluminum Overall
<b>Surface Treatment Document And Classification:</b>	Nas 4006 Assn Std Single Treatment Response Overall

## How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/LGPL2SP-V06-04AC> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.