

**Description**

Fastener Length: 11/16", Thread: 1/4-20, Thread Length: 37/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |                                           |
|-------------------------|-------------------------------------------|
| SKU / Model:            | LL200740405                               |
| Minimum Qty (MOQ):      | 5 EA                                      |
| NSN:                    | 5306-00-947-0178                          |
| Schedule B:             | 7318.15.8085                              |
| ECCN:                   | 9A991                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N LL20074-04-05 Specifications

|                                                       |                                                                                                                                                                                                                                                                                                                          |
|-------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Thread Class:</b>                                  | 3a                                                                                                                                                                                                                                                                                                                       |
| <b>Thread Direction:</b>                              | Right-hand                                                                                                                                                                                                                                                                                                               |
| <b>Thread Length:</b>                                 | 0.500 Inches Minimum And 0.579 Inches Maximum                                                                                                                                                                                                                                                                            |
| <b>Fastener Length:</b>                               | 0.641 Inches Minimum And 0.688 Inches Maximum                                                                                                                                                                                                                                                                            |
| <b>Head Style:</b>                                    | Hexagon                                                                                                                                                                                                                                                                                                                  |
| <b>Head Height:</b>                                   | 0.203 Inches Minimum And 0.234 Inches Maximum                                                                                                                                                                                                                                                                            |
| <b>Width Between Flats:</b>                           | 0.430 Inches Minimum And 0.439 Inches Maximum                                                                                                                                                                                                                                                                            |
| <b>Locking Feature:</b>                               | Strip Threads                                                                                                                                                                                                                                                                                                            |
| <b>Nominal Thread Diameter:</b>                       | 0.250 Inches                                                                                                                                                                                                                                                                                                             |
| <b>Grip Length:</b>                                   | 0.109 Inches Minimum And 0.141 Inches Maximum                                                                                                                                                                                                                                                                            |
| <b>Features Provided:</b>                             | Finished Head                                                                                                                                                                                                                                                                                                            |
| <b>Thread Quantity Per Inch:</b>                      | 20                                                                                                                                                                                                                                                                                                                       |
| <b>Minimum Tensile Strength:</b>                      | 125000 Pounds Per Square Inch                                                                                                                                                                                                                                                                                            |
| <b>Hardness Rating:</b>                               | 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall                                                                                                                                                                                                                                                      |
| <b>Special Features:</b>                              | 6 Drilled Holes 0.070 In. Dia In Head                                                                                                                                                                                                                                                                                    |
| <b>Material:</b>                                      | Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall                                                                                                                                                           |
| <b>Material Document And Classification:</b>          | Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall |
| <b>Surface Treatment:</b>                             | Cadmium Overall And Chromate Overall                                                                                                                                                                                                                                                                                     |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Overall                                                                                                                                                                                                                                                       |
| <b>Thread Series Designator:</b>                      | Unc                                                                                                                                                                                                                                                                                                                      |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/LL20074-04-05> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.