

Description

Fastener Length: 5/16", Thread: 5-40, Thread Length: 5/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	LL22A50S5M
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-027-5236
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N LL22A50S5M Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.231 Inches Minimum And 0.312 Inches Maximum
Fastener Length:	0.281 Inches Minimum And 0.312 Inches Maximum
Head Style:	Round
Head Diameter:	0.217 Inches Minimum And 0.236 Inches Maximum
Head Height:	0.095 Inches Maximum
Locking Feature:	Strip Threads
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.125 Inches
Thread Quantity Per Inch:	40
Material:	Plastic Locking Feature
Material:	Steel Comp 1010 Fastener
Surface Treatment:	Cadmium Fastener
Surface Treatment Document And Classification:	Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response Fastener
Thread Series Designator:	Unc

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/LL22A50S5M> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.