

P/N LL500-4-4

Description

Fastener Length: 1/4", Thread: 4-40, Thread Length: 1/4"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

| SKU / Model: | LL50044 |
|--------------------|------------------|
| Minimum Qty (MOQ): | 15 EA |
| NSN: | 5305-01-518-6228 |
| Schedule B: | 7318.15.6080 |
| ECCN: | 9A991 |



^{*} See page 2 for technical characteristics

P/N LL500-4-4 Specifications

| Thread Class: | 2a |
|--|---|
| Thread Direction: | Right-hand |
| Thread Length: | 0.200 Inches Minimum And 0.250 Inches Maximum |
| Fastener Length: | 0.219 Inches Minimum And 0.250 Inches Maximum |
| Head Style: | Fillister |
| Head Diameter: | 0.166 Inches Minimum And 0.183 Inches Maximum |
| Head Height: | 0.072 Inches Minimum And 0.079 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| End Item Identification: | Hawkeye Aircraft |
| Nominal Thread Diameter: | 0.112 Inches |
| Thread Quantity Per Inch: | 40 |
| Minimum Tensile Strength: | 60000 Pounds Per Square Inch |
| Part Name Assigned By Controlling Agency: | Screw, Machine, Fillister Head, Coarse Thread |
| Screw Material: | Steel Or Steel Comp 1010 |
| Screw Material Document And Classification: | Qq-s-630 Fed Spec 2nd Material Response Or Qq-s-631 Fed Spec 2nd Material Response Or Qq-s-634 Fed Spec 2nd Material Response |
| Screw Surface Treatment: | Cadmium |
| Screw Surface Treatment Document And Classification: | Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response |
| Special Features: | With Self-locking Element |
| Thread Series Designator: | Unc |

How to Order

Order this screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/LL500-4-4 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.