

Description

Fastener Length: 1/2", Thread: 6-32, Thread Length: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	LL50068M
Minimum Qty (MOQ):	55 EA
NSN:	5305-00-836-7177
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N LL500-6-8M Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.500 Inches Minimum
Fastener Length:	0.500 Inches Nominal
Head Style:	Fillister
Head Diameter:	0.226 Inches Maximum
Head Height:	0.132 Inches Maximum
Locking Feature:	Strip Threads
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.138 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	60000 Pounds Per Square Inch
Material:	Steel Comp 1010 Overall
Material Document And Classification:	Qq-s-630 Fed Spec Single Material Response Overall Or Qq-s-631 Fed Spec Single Material Response Overall Or Qq-s-634 Fed Spec Single Material Response Overall
Surface Treatment:	Cadmium Overall
Thread Series Designator:	Unc

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/LL500-6-8M> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.