

**Description**

Fastener Length: 3/16", Thread: 5-40, Thread Length: 1/8"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	LL515PB53
Minimum Qty (MOQ):	15 EA
NSN:	5305-00-918-4945
Schedule B:	7318.15.2091
ECCN:	EAR99
National Motor Freight:	096630, Screws Noi Brass / Bronze / Copper

NO IMAGE  
AVAILABLE

## P/N LL515PB5-3 Specifications

<b>Thread Class:</b>	2a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.138 Inches Minimum
<b>Fastener Length:</b>	0.188 Inches Nominal
<b>Head Style:</b>	Round
<b>Head Diameter:</b>	0.217 Inches Minimum And 0.236 Inches Maximum
<b>Head Height:</b>	0.095 Inches Nominal
<b>Locking Feature:</b>	Patch Threads
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.125 Inches
<b>Thread Quantity Per Inch:</b>	40
<b>Minimum Tensile Strength:</b>	55000 Pounds Per Square Inch
<b>Material:</b>	Copper Alloy Overall
<b>Material Document And Classification:</b>	Qq-b-613 Fed Spec Single Material Response Overall Or Qq-b-626 Fed Spec Single Material Response Overall Or Qq-w-321 Fed Spec Single Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Thread Series Designator:</b>	Unc
<b>Nondefinitive Spec/std Data:</b>	3 Type And 1c Style
<b>Departure From Cited Designator:</b>	As Mod By Locking Feature

## How to Order

Order this screwlock from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/LL515PB5-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.