

Description

Fastener Length: 3/16", Thread: 5-40, Thread Length: 1/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|--|
| SKU / Model: | LL515PB53 |
| Minimum Qty (MOQ): | 15 EA |
| NSN: | 5305-00-918-4945 |
| Schedule B: | 7318.15.2091 |
| ECCN: | EAR99 |
| National Motor Freight: | 096630, Screws Noi Brass / Bronze / Copper |

NO IMAGE
AVAILABLE

P/N LL515PB5-3 Specifications

| | |
|--|--|
| Thread Class: | 2a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.138 Inches Minimum |
| Fastener Length: | 0.188 Inches Nominal |
| Head Style: | Round |
| Head Diameter: | 0.217 Inches Minimum And 0.236 Inches Maximum |
| Head Height: | 0.095 Inches Nominal |
| Locking Feature: | Patch Threads |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.125 Inches |
| Thread Quantity Per Inch: | 40 |
| Minimum Tensile Strength: | 55000 Pounds Per Square Inch |
| Material: | Copper Alloy Overall |
| Material Document And Classification: | Qq-b-613 Fed Spec Single Material Response Overall Or Qq-b-626 Fed Spec Single Material Response Overall Or Qq-w-321 Fed Spec Single Material Response Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Thread Series Designator: | Unc |
| Nondefinitive Spec/std Data: | 3 Type And 1c Style |
| Departure From Cited Designator: | As Mod By Locking Feature |

How to Order

Order this screwlock from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/LL515PB5-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.