

Description

Fastener Length: 3/16", Thread: 5-40, Thread Length: 1/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	LL515PB53
Minimum Qty (MOQ):	15 EA
NSN:	5305-00-918-4945
Schedule B:	7318.15.2091
ECCN:	EAR99
National Motor Freight:	096630, Screws Noi Brass / Bronze / Copper

NO IMAGE
AVAILABLE

P/N LL515PB5-3 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.138 Inches Minimum
Fastener Length:	0.188 Inches Nominal
Head Style:	Round
Head Diameter:	0.217 Inches Minimum And 0.236 Inches Maximum
Head Height:	0.095 Inches Nominal
Locking Feature:	Patch Threads
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.125 Inches
Thread Quantity Per Inch:	40
Minimum Tensile Strength:	55000 Pounds Per Square Inch
Material:	Copper Alloy Overall
Material Document And Classification:	Qq-b-613 Fed Spec Single Material Response Overall Or Qq-b-626 Fed Spec Single Material Response Overall Or Qq-w-321 Fed Spec Single Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Thread Series Designator:	Unc
Nondefinitive Spec/std Data:	3 Type And 1c Style
Departure From Cited Designator:	As Mod By Locking Feature

How to Order

Order this screwlock from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/LL515PB5-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.