

Description

Fastener Length: 7/32", Thread: 4-40, Thread Length: 11/64

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	LL5195713
Minimum Qty (MOQ):	20 EA
NSN:	5305-00-150-3325
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N LL51957-13 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.169 Inches Minimum And 0.250 Inches Maximum
Fastener Length:	0.219 Inches Minimum And 0.250 Inches Maximum
Head Style:	Pan
Head Diameter:	0.205 Inches Minimum And 0.219 Inches Maximum
Head Height:	0.070 Inches Minimum And 0.080 Inches Maximum
Locking Feature:	Strip Threads
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.112 Inches
Thread Quantity Per Inch:	40
Material:	Steel Corrosion Resisting Overall Or Steel Overall
Material Document And Classification:	Qq-s-763,300 Series Fed Spec 1st Material Response Overall Or 66,300 Series Fed Std 1st Material Response Overall Or Comp 16-18 Or 18-8 Assn Std 2nd Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unc

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/LL51957-13> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.