

Description

Fastener Length: 7/32", Thread: 4-40, Thread Length: 11/64

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | LL54N40S4 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5305-00-465-3074 |
| Schedule B: | 7318.15.6080 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N LL54N40S4 Specifications

| | |
|---|--|
| Thread Class: | 2a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.169 Inches Minimum And 0.250 Inches Maximum |
| Fastener Length: | 0.219 Inches Minimum And 0.250 Inches Maximum |
| Head Style: | Fillister |
| Head Diameter: | 0.166 Inches Minimum And 0.183 Inches Maximum |
| Head Height: | 0.072 Inches Minimum And 0.079 Inches Maximum |
| Locking Feature: | Strip Threads |
| Internal Drive Style: | Slot |
| Nominal Thread Diameter: | 0.112 Inches |
| Thread Quantity Per Inch: | 40 |
| Material: | Steel Comp 302 Overall Or Steel Comp 304 Overall Or Steel Comp 316 Overall Or Steel Comp 303se Overall |
| Material Document And Classification: | 66 Fed Std All Material Responses Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unc |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/LL54N40S4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.