

P/N LL54N40S4

Description

Fastener Length: 7/32", Thread: 4-40, Thread Length: 11/64

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: LL54N40S4

Minimum Qty (MOQ): 5 EA

NSN: 5305-00-465-3074

Schedule B: 7318.15.6080

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N LL54N40S4 Specifications

| Thread Class: | 2a |
|--|--|
| Thread Direction: | Right-hand |
| Thread Length: | 0.169 Inches Minimum And 0.250 Inches Maximum |
| Fastener Length: | 0.219 Inches Minimum And 0.250 Inches Maximum |
| Head Style: | Fillister |
| Head Diameter: | 0.166 Inches Minimum And 0.183 Inches Maximum |
| Head Height: | 0.072 Inches Minimum And 0.079 Inches Maximum |
| Locking Feature: | Strip Threads |
| Internal Drive Style: | Slot |
| Nominal Thread Diameter: | 0.112 Inches |
| Thread Quantity Per Inch: | 40 |
| Material: | Steel Comp 302 Overall Or Steel Comp 304 Overall Or Steel Comp 316 Overall Or Steel Comp 303se Overall |
| Material Document And Classification: | 66 Fed Std All Material Responses Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unc |

How to Order

Order this screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/LL54N40S4 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.