

Description

Fastener Length: 11/64", Thread: 4-40, Thread Length: 1/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	LL57J40P3
Minimum Qty (MOQ):	30 EA
NSN:	5305-00-688-7689
Schedule B:	7318.15.6080
ECCN:	EAR99



* See page 2 for technical characteristics

P/N LL57J40P3 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.060 Inches Minimum And 0.150 Inches Maximum
Fastener Length:	0.157 Inches Minimum And 0.188 Inches Maximum
Head Style:	Flat Countersunk Undercut
Head Diameter:	0.195 Inches Minimum And 0.225 Inches Maximum
Head Height:	0.038 Inches Minimum And 0.047 Inches Maximum
Locking Feature:	Strip Threads
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.112 Inches
Thread Quantity Per Inch:	40
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Countersink Angle:	80.0 Degrees Minimum And 82.0 Degrees Maximum
Material:	Steel Comp 410 Overall Or Steel Comp 416 Overall
Material Document And Classification:	Qq-s-763 Fed Spec 1st Material Response Overall Or Qq-s-764 Fed Spec 2nd Material Response Overall
Surface Treatment:	Passivate Overall
Thread Series Designator:	Unc

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/LL57J40P3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.