

**Description**

Fastener Length: 11/64", Thread: 4-40, Thread Length: 1/16"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	LL57J40P3
Minimum Qty (MOQ):	30 EA
NSN:	5305-00-688-7689
Schedule B:	7318.15.6080
ECCN:	EAR99

NO IMAGE  
AVAILABLE

## P/N LL57J40P3 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.060 Inches Minimum And 0.150 Inches Maximum
<b>Fastener Length:</b>	0.157 Inches Minimum And 0.188 Inches Maximum
<b>Head Style:</b>	Flat Countersunk Undercut
<b>Head Diameter:</b>	0.195 Inches Minimum And 0.225 Inches Maximum
<b>Head Height:</b>	0.038 Inches Minimum And 0.047 Inches Maximum
<b>Locking Feature:</b>	Strip Threads
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.112 Inches
<b>Thread Quantity Per Inch:</b>	40
<b>Minimum Tensile Strength:</b>	80000 Pounds Per Square Inch
<b>Countersink Angle:</b>	80.0 Degrees Minimum And 82.0 Degrees Maximum
<b>Material:</b>	Steel Comp 410 Overall Or Steel Comp 416 Overall
<b>Material Document And Classification:</b>	Qq-s-763 Fed Spec 1st Material Response Overall Or Qq-s-764 Fed Spec 2nd Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Thread Series Designator:</b>	Unc

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/LL57J40P3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.