

Description

Fastener Length: 1/4", Thread: 10-32, Head Width: 3/32", Thread Length: 5/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	LP12XC02J4
Minimum Qty (MOQ):	10 EA
NSN:	5305-00-520-2827
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	096630, Screws Noi Brass / Bronze / Copper

NO IMAGE
AVAILABLE

P/N LP12XC02J4 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.150 Inches Minimum And 0.170 Inches Maximum
Fastener Length:	0.240 Inches Minimum And 0.260 Inches Maximum
Head Style:	Headless (setscrew)
Point Style:	Full Dog
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.190 Inches
Width Across Flats:	0.094 Inches Minimum And 0.095 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	38.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall
Material:	Steel Overall
Surface Treatment:	Cadmium Overall
Thread Series Designator:	Unf

How to Order

Order this screwlock from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/LP12XC02J4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.