

Description

Fastener Length: 13/16", Thread: 1/4-20, Thread Length: 37/64"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	LP200740406
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-094-0336
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N LP20074-04-06 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.499 Inches Minimum And 0.578 Inches Maximum
Fastener Length:	0.765 Inches Minimum And 0.812 Inches Maximum
Head Style:	Hexagon
Head Height:	0.203 Inches Minimum And 0.234 Inches Maximum
Width Between Flats:	0.430 Inches Minimum And 0.439 Inches Maximum
Locking Feature:	Strip Threads
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.234 Inches Minimum And 0.266 Inches Maximum
Features Provided:	Finished Head
Thread Quantity Per Inch:	20
Special Features:	6 Drilled Holes 0.070 In. Dia In Head
Material:	Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unc

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/LP20074-04-06> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.