

Description

Fastener Length: 3/4", Thread: 10-24, Thread Length: 3/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	LP5001012M
Minimum Qty (MOQ):	10 EA
NSN:	5305-00-052-9297
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N LP500-10-12M Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.750 Inches Minimum
Fastener Length:	0.750 Inches Nominal
Head Style:	Fillister
Head Diameter:	0.292 Inches Minimum And 0.313 Inches Maximum
Head Height:	0.118 Inches Minimum And 0.130 Inches Maximum
Locking Feature:	Strip Threads
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	24
Material:	Steel Comp 1010 Overall
Material Document And Classification:	Qq-s-634 Fed Spec Single Material Response Overall
Surface Treatment:	Cadmium Overall
Thread Series Designator:	Unc

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/LP500-10-12M> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.