

Description

Fastener Length: 3-11/64", Thread: 7/8-14, Thread Length: 1-11/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	LWB221432
Minimum Qty (MOQ):	1 EA
NSN:	5306-00-067-6380
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N LWB22-14-32 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.175 Inches Minimum
Fastener Length:	3.175 Inches Nominal
Head Style:	Double Hexagon W/hole
Head Height:	0.808 Inches Nominal
Width Between Flats:	0.923 Inches Minimum And 0.940 Inches Maximum
Extended Washer Diameter:	1.433 Inches Nominal
Extended Washer Thickness:	0.198 Inches Nominal
Grip Diameter:	0.8730 Inches Minimum And 0.8740 Inches Maximum
Single Shear Strength:	132000 Pounds Per Square Inch
Nominal Thread Diameter:	0.875 Inches
Grip Length:	2.000 Inches Nominal
Thread Quantity Per Inch:	14
Minimum Tensile Strength:	220000 Pounds Per Square Inch
Hardness Rating:	46.0 Rockwell C Minimum Overall And 50.0 Rockwell C Maximum Overall
Material:	Steel Comp H11 Overall
Material Document And Classification:	Ams6485 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Nas 672 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/LWB22-14-32> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.