

**Description**

Fastener Length: 57/64", Thread: 10-32, Thread Length: 21/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | LWB2239                                   |
| Minimum Qty (MOQ):      | 1 EA                                      |
| NSN:                    | 5306-00-917-0902                          |
| Schedule B:             | 7318.15.8085                              |
| ECCN:                   | 9A991                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N LWB22-3-9 Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>                                  | 3a  |
| <b>Thread Direction:</b>                              | Right-hand  |
| <b>Thread Length:</b>                                 | 0.334 Inches Minimum  |
| <b>Fastener Length:</b>                               | 0.896 Inches Nominal  |
| <b>Head Style:</b>                                    | Double Hexagon W/hole   |
| <b>Head Height:</b>                                   | 0.275 Inches Nominal  |
| <b>Width Between Flats:</b>                           | 0.243 Inches Minimum And 0.251 Inches Maximum   |
| <b>Extended Washer Diameter:</b>                      | 0.345 Inches Nominal  |
| <b>Extended Washer Thickness:</b>                     | 0.064 Inches Nominal  |
| <b>Grip Diameter:</b>                                 | 0.1885 Inches Minimum And 0.1895 Inches Maximum   |
| <b>Nominal Thread Diameter:</b>                       | 0.190 Inches  |
| <b>Grip Length:</b>                                   | 0.562 Inches Nominal  |
| <b>Thread Quantity Per Inch:</b>                      | 32  |
| <b>Minimum Tensile Strength:</b>                      | 220000 Pounds Per Square Inch   |
| <b>Hardness Rating:</b>                               | 46.0 Rockwell C Minimum Overall And 50.0 Rockwell C Maximum Overall                                     |
| <b>Material:</b>                                      | Steel Comp H11 Overall  |
| <b>Material Document And Classification:</b>          | Ams 6485 Assn Std Single Material Response Overall Or Ams6487 Assn Std Single Material Response Overall |
| <b>Surface Treatment:</b>                             | Cadmium Overall   |
| <b>Surface Treatment Document And Classification:</b> | Nas 672 Assn Std Single Treatment Response Overall  |
| <b>Thread Series Designator:</b>                      | Unjf  |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/LWB22-3-9> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.