

Description

Fastener Length: 1-47/64", Hole Diameter: ", Thread: 1/4-24, Thread Length: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	LWB225H20
Minimum Qty (MOQ):	1 EA
NSN:	5306-00-488-3862
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N LWB22-5H20 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.455 Inches Minimum And 0.505 Inches Maximum
Fastener Length:	1.715 Inches Minimum And 1.745 Inches Maximum
Head Style:	Double Hexagon W/hole
Head Height:	0.338 Inches Minimum And 0.358 Inches Maximum
Width Between Flats:	0.367 Inches Minimum And 0.376 Inches Maximum
Extended Washer Diameter:	0.521 Inches Minimum And 0.531 Inches Maximum
Extended Washer Thickness:	0.072 Inches Minimum And 0.092 Inches Maximum
Hole Diameter:	0.055 Inches Nominal
Grip Diameter:	0.3110 Inches Minimum And 0.3120 Inches Maximum
Nominal Thread Diameter:	0.312 Inches
Grip Length:	1.240 Inches Minimum And 1.260 Inches Maximum
Hole Quantity:	4
Hole Type:	Drilled
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	220000 Pounds Per Square Inch
Hardness Rating:	46.0 Rockwell C Minimum Overall And 50.0 Rockwell C Maximum Overall
Hole Configuration Style:	Round
Material:	Steel Comp H11 Overall
Material Document And Classification:	Ams 6485 Assn Std Single Material Response Overall Or Ams6487 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Nas 672 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/LWB22-5H20> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.