

Description

Retaining Ring part number

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|-----------------------------|
| SKU / Model: | M2742630105B |
| Minimum Qty (MOQ): | 10 EA |
| NSN: | 5325-00-988-5319 |
| Schedule B: | 7318.29.0000 |
| ECCN: | EAR99 |
| National Motor Freight: | 095190, Hardware, Noi Sub 9 |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N M2742630105B Specifications

| | |
|--|---|
| Cross-sectional Shape Style: | Double Oval |
| Inside Diameter: | 0.568 Inches Nominal |
| Casehardening Indicator: | Not Casehardened |
| Outside Diameter: | 0.658 Inches Minimum And 0.671 Inches Maximum |
| Major Thickness: | 0.023 Inches Minimum And 0.027 Inches Maximum |
| Ring Style: | Spiral |
| Usage Design: | Internal |
| Material Hardness Rating: | 71.0 Rockwell A Minimum And 77.5 Rockwell A Maximum |
| Strength Rating: | 221000.0 Pounds Per Square Inch Minimum Tensile |
| Material: | Steel, Mil-s-46049, Comp 1074 Or Steel, Mil-s-46049, Comp 1085 |
| Material: | Steel Comp 1074 Or Steel Comp 1085 |
| Material Document And Classification: | Mil-s-46049, Comp 1074 Mil Spec 1st Material Response And Mil-s-46049, Comp 1085 Mil Spec 2nd Material Response |
| Surface Treatment: | Cadmium And Chromate |
| Surface Treatment: | Cadmium, Qq-p-416, Type 2, Class 2 |

How to Order

Order this retaining ring from our inventory online by visiting <https://military-fasteners.com/rings/retaining+rings/M2742630105B> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.