

# P/N M2742630170C

### **Description**

Ret. Ring part number

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

# Order this part online

#### **Additional Information**

SKU / Model:	M2742630170C
Minimum Qty (MOQ):	1 EA
NSN:	5325-00-159-2655
Schedule B:	7318.29.0000
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi



<sup>\*</sup> See page 2 for technical characteristics

# P/N M2742630170C Specifications

Cross-sectional Shape Style:	Rectangular
Inside Diameter:	2.730 Inches Minimum And 2.755 Inches Maximum
Casehardening Indicator:	Not Casehardened
Outside Diameter:	3.046 Inches Minimum And 3.071 Inches Maximum
Major Thickness:	0.029 Inches Minimum And 0.033 Inches Maximum
Ring Style:	Special
Usage Design:	Internal
Material:	Steel,fed Std 66,aisi Or Sae 1070 Thru 1090
Material:	Steel,fed Std 66,aisi Or Sae 1070 Thru 1090
Surface Treatment:	Oxide
Surface Treatment:	Black Oxide, Mil-c-13924, Class 1

## **How to Order**

Order this ret. ring from our inventory online by visiting <a href="https://military-fasteners.com/rings/retaining+rings/M2742630170C">https://military-fasteners.com/rings/retaining+rings/M2742630170C</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rings/retaining+rings/M2742630170C">https://military-fasteners.com/rings/retaining+rings/M2742630170C</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rings/retaining+rings/M2742630170C">https://military-fasteners.com/rings/retaining+rings/M2742630170C</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rings/retaining+rings/M2742630170C">https://military-fasteners.com/rings/retaining+rings/M2742630170C</a> and selecting the quantity you want out <a href="https://military-fasteners.com/rings/retaining+rings/M2742630170C">https://military-fasteners.com/rings/retaining+rings/M2742630170C</a> and selecting the quantity you want <a href="https://military-fasteners.com/rings/retaining-rings/m2742630170C">https://military-fasteners.com/rings/retaining-rings/m2742630170C</a> and selecting the quantity you want <a href="https://military-fasteners.com/rings/retaining-rings/m2742630170C">https://military-fasteners.com/rings/retaining-rings/m2742630170C</a> and selecting the quantity you want <a href="https://military-fasteners.com/rings/retaining-rings/m2742630170C">https://military-fasteners.com/rings/retaining-rings/m2742630170C</a> and selecting the quantity you want <a href="https://military-fasteners.com/rings/m2742630170C">https://military-fasteners.com/rings/m2742630170C</a> are selecting the property of the pro