

P/N M2742630173D

Description

Retaining Ring part number

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

 SKU / Model:
 M2742630173D

 Minimum Qty (MOQ):
 10 EA

NSN: 5325-01-172-0360

Schedule B: 7318.15.2010

ECCN: 9A991



^{*} See page 2 for technical characteristics

P/N M2742630173D Specifications

| Cross-sectional Shape Style: | Double Oval |
|--|---|
| Inside Diameter: | 3.186 Inches Minimum And 3.211 Inches Maximum |
| Casehardening Indicator: | Not Casehardened |
| Outside Diameter: | 3.537 Inches Minimum And 3.628 Inches Maximum |
| Major Thickness: | 0.058 Inches Minimum And 0.064 Inches Maximum |
| Ring Style: | Special Flat |
| Usage Design: | Internal |
| Material Hardness Rating: | 72.0 Rockwell C Minimum And 74.9 Rockwell C Maximum |
| Material: | Steel, Fed Std 66, Aisi 302/sae 30302 Or Steel, Mil-s-5059, Type 302 |
| Material: | Steel Comp 302 Or Steel Comp 302 |
| Material Document And Classification: | Fed Std 66 Fed Std 1st Material Response Or Aisi 302 Assn Std Single Material Response Or Sae 30302 Assn Std Single Material Response And Mil-s-5059, Type 302 Mil Spec 2nd Material Response |
| Surface Treatment: | Passivate |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response |
| Surface Treatment: | Passivated, Qq-p-35 |
| Nondefinitive Spec/std Data: | B Type And 1 Class |

How to Order

Order this retaining ring from our inventory online by visiting https://military-fasteners.com/rings/retaining+rings/M2742630173D and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.