

Description

Retaining Ring part number

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	M2742640100D
Minimum Qty (MOQ):	10 EA
NSN:	5325-00-163-6664
Schedule B:	7318.15.5030
ECCN:	9A991
National Motor Freight:	095190, Hardware, Noi Sub 9



* See page 2 for technical characteristics

P/N M2742640100D Specifications

Cross-sectional Shape Style:	Double Oval
Inside Diameter:	0.448 Inches Minimum And 0.461 Inches Maximum
Casehardening Indicator:	Not Casehardened
Outside Diameter:	0.538 Inches Minimum And 0.551 Inches Maximum
Major Thickness:	0.033 Inches Minimum And 0.037 Inches Maximum
Ring Style:	Spiral
Usage Design:	Internal
Strength Rating:	200000.0 Pounds Per Square Inch Minimum Tensile
Material:	Steel, Sae 302 Or Steel, Aisi 302 Or Steel, Mil-s-5059, Type 302 Or Steel, Ams 5688 Or Steel, Qq-s-766, Class 302
Material:	Steel Comp 302 Or Steel Comp 302 Or Steel Comp 302 Or Steel Comp 302 Or Steel Comp 302
Material Document And Classification:	Sae 302 Assn Std 1st Material Response And Aisi 302 Assn Std 2nd Material Response And Mil-s-5059, Type 302 Mil Spec 3rd Material Response And Ams 5688 Assn Std 4th Material Response And Qq-s-766, Class 302 Fed Spec 5th Material Response
Surface Treatment:	Passivate
Surface Treatment:	Passivated, Qq-p-35

How to Order

Order this retaining ring from our inventory online by visiting <https://military-fasteners.com/rings/retaining+rings/M2742640100D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.