

Description

M81935-1-04K Rod End Bearing

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	M81935104K
Minimum Qty (MOQ):	1
NSN:	3120-01-102-5652
ECCN:	EAR99
National Motor Freight:	114820, Bearings / Bushings Noi Ball / Roller



* See page 2 for technical characteristics

P/N M81935-1-04K Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Shank Style:	Externally Threaded
Overall Length:	1.9650 Inches Nominal
Bore Diameter:	0.2495 Inches Minimum And 0.2500 Inches Maximum
Outer Member Outside Diameter:	0.7960 Inches Minimum And 0.8160 Inches Maximum
Bore Center To Shank End Distance:	1.5520 Inches Minimum And 1.5720 Inches Maximum
Outer Member Width:	0.3320 Inches Minimum And 0.3420 Inches Maximum
Inner Member Width:	0.4350 Inches Minimum And 0.4370 Inches Maximum
Shank Thread Length:	0.9370 Inches Minimum And 0.9990 Inches Maximum
Static Radial Load Rating:	4860 Pounds
Thread Diameter:	0.312 Inches Nominal
Thread Quantity Per Inch:	24
Hardness Rating:	28.0 Rockwell C Minimum Race Insert And 37.0 Rockwell C Maximum Race Insert
Hardness Rating:	39.0 Rockwell C Minimum Rod End Body And 42.0 Rockwell C Maximum Rod End Body
Hardness Rating:	55.0 Rockwell C Minimum Inner Member And 62.0 Rockwell C Maximum Inner Member
Special Features:	Keyway In Shank
Material:	Plastic Polytetrafluoroethylene Race Liner
Material:	Steel Comp 440c Inner Member
Material:	Steel Comp E4340 Rod End Body
Material:	Steel Comp 630 Race Insert
Style Designator:	Ball Type
Thread Series Designator:	Unjf

How to Order

Order this rod end bearing from our inventory online by visiting <https://military-fasteners.com/bearings/rod+end+bearings/M81935-1-04K> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.