

Description

Hole Diameter: 13-5/16", Diameter: 20-1/2", Thickness: 2-5/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MA3453120
Minimum Qty (MOQ):	5 EA
NSN:	5310-01-597-1840
Schedule B:	7318.22.0000
ECCN:	EAR99
National Motor Freight:	194160, Washer Or Gaskets, Iron Or Steel,

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MA3453-120 Specifications

Cross-sectional Shape Style:	Rectangular
Hole Diameter:	13.3 Millimeters Minimum And 13.5 Millimeters Maximum
Peripheral Shape Style:	Round
Center Hole Shape Style:	1 Round
Thickness:	2.3 Millimeters Minimum And 2.7 Millimeters Maximum
Overall Diameter:	20.5 Millimeters Minimum And 21.0 Millimeters Maximum
Hardness Rating:	24.0 Rockwell C Minimum And 35.0 Rockwell C Maximum Or 247.0 Rockwell B Minimum And 327.0 Rockwell B Maximum
Part Name Assigned By Controlling Agency:	Washer, Flat, Ams-5525, Metric
Special Features:	Precipitation Heat Treat Per Ams-2759/3; Hardness Also 260-345 Hv
Material:	Steel Corrosion Resisting Overall
Material Document And Classification:	Ams-5525 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Ma1784 Fed Std Single Treatment Response Overall

How to Order

Order this metric washer from our inventory online by visiting <https://military-fasteners.com/washers/flat+washers/MA3453-120> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.