

Description

Fastener Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MD440BS
Minimum Qty (MOQ):	75 EA
NSN:	5320-00-987-2985
Schedule B:	7318.23.0000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets

NO IMAGE
AVAILABLE

P/N MD440BS Specifications

Fastener Length:	0.390 Inches Minimum And 0.420 Inches Maximum
Head Style:	Universal
Head Height:	0.020 Inches Minimum And 0.030 Inches Maximum
Shank Diameter:	0.123 Inches Minimum And 0.128 Inches Maximum
Shank Style:	Self-plugging
Head Major Diameter:	0.224 Inches Minimum And 0.248 Inches Maximum
Expansion Device:	Mandrel-type C
Grip Length:	0.188 Inches Minimum And 0.250 Inches Maximum
Shear Strength:	385 Double Pounds Per Square Inch
Material:	Nickel Alloy 400 Body
Material:	Steel Mandrel
Material Document And Classification:	Qq-n-281,cl A Fed Spec Single Material Response Body

How to Order

Order this pop rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MD440BS> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.