

Description

Fastener Length: 3/8"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MD440BS
Minimum Qty (MOQ):	75 EA
NSN:	5320-00-987-2985
Schedule B:	7318.23.0000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



\* See page 2 for technical characteristics

## P/N MD440BS Specifications

<b>Fastener Length:</b>	0.390 Inches Minimum And 0.420 Inches Maximum
<b>Head Style:</b>	Universal
<b>Head Height:</b>	0.020 Inches Minimum And 0.030 Inches Maximum
<b>Shank Diameter:</b>	0.123 Inches Minimum And 0.128 Inches Maximum
<b>Shank Style:</b>	Self-plugging
<b>Head Major Diameter:</b>	0.224 Inches Minimum And 0.248 Inches Maximum
<b>Expansion Device:</b>	Mandrel-type C
<b>Grip Length:</b>	0.188 Inches Minimum And 0.250 Inches Maximum
<b>Shear Strength:</b>	385 Double Pounds Per Square Inch
<b>Material:</b>	Nickel Alloy 400 Body
<b>Material:</b>	Steel Mandrel
<b>Material Document And Classification:</b>	Qq-n-281,cl A Fed Spec Single Material Response Body

## How to Order

Order this pop rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MD440BS> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.