

Description

Fastener Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MLS100M45C
Minimum Qty (MOQ):	5 EA
NSN:	5320-00-761-5993
Schedule B:	7508.90.5000
ECCN:	9A991
National Motor Freight:	061680, Elec Wiring Plugs Etc

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MLS100M4-5C Specifications

Fastener Length:	0.406 Inches Minimum And 0.426 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Head Height:	0.042 Inches Nominal
Shank Diameter:	0.124 Inches Minimum And 0.128 Inches Maximum
Head Major Diameter:	0.221 Inches Minimum And 0.229 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.251 Inches Minimum And 0.312 Inches Maximum
Minimum Tensile Strength:	675 Pounds Per Square Inch
Shear Strength:	1020 Single Pounds Per Square Inch
Countersink Angle:	98.5 Degrees Minimum And 101.5 Degrees Maximum
Material:	Nickel Alloy 400 Overall Or Steel Overall
Material Document And Classification:	Aisi 630 Assn Std 2nd Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416 Type 2 Class 3 Fed Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1921 Professional/industrial Association Standard

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MLS100M4-5C> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.