

Description

Fastener Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---------------------|
| SKU / Model: | MLSPB0504 |
| Minimum Qty (MOQ): | 10 EA |
| NSN: | 5320-00-194-9794 |
| Schedule B: | 7616.10.3000 |
| ECCN: | EAR99 |
| National Motor Freight: | 013630, Alum Rivets |

NO IMAGE
AVAILABLE

P/N MLSP-B05-04 Specifications

| | |
|---|--|
| Fastener Length: | 0.388 Inches Maximum |
| Head Style: | Universal |
| Head Height: | 0.067 Inches Minimum And 0.077 Inches Maximum |
| Shank Diameter: | 0.155 Inches Minimum And 0.159 Inches Maximum |
| Shank Style: | Self-plugging Mechanically Locked Stem |
| Head Major Diameter: | 0.296 Inches Minimum And 0.328 Inches Maximum |
| Expansion Device: | Serrated Stem-type W |
| Grip Length: | 0.188 Inches Minimum And 0.250 Inches Maximum |
| Shear Strength: | 755 Single Pounds Per Square Inch |
| Special Features: | Self-locking |
| Material: | Aluminum Alloy 5056 Sleeve Or Aluminum Alloy 2024 Sleeve |
| Material: | Aluminum Alloy 5056 Stem Or Aluminum Alloy 2024 Stem |
| Material Document And Classification: | Qq-a-430 Fed Spec Single Material Response Sleeve |
| Material Document And Classification: | Qq-a-430 Fed Spec Single Material Response Stem |
| Surface Treatment: | Chromate Stem |
| Surface Treatment: | Anodize Sleeve |
| Surface Treatment Document And Classification: | Mil-a-8625 Mil Spec 1st Treatment Response Sleeve |
| Surface Treatment Document And Classification: | Mil-c-5541 Mil Spec 1st Treatment Response Stem |
| Specification/standard Data: | 80205-nas1919 Professional/Industrial Association Standard |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MLSP-B05-04> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.