

Description

Fastener Length: 9/16"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MLSPEU0403
Minimum Qty (MOQ):	10 EA
NSN:	5320-00-403-0234
Schedule B:	7318.23.0000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



\* See page 2 for technical characteristics

## P/N MLSP-EU04-03 Specifications

<b>Fastener Length:</b>	0.568 Inches Nominal
<b>Head Style:</b>	Universal
<b>Head Height:</b>	0.054 Inches Minimum And 0.064 Inches Maximum
<b>Shank Diameter:</b>	0.124 Inches Minimum And 0.128 Inches Maximum
<b>Shank Style:</b>	Self-plugging Mechanically Locked Stem
<b>Head Major Diameter:</b>	0.242 Inches Minimum And 0.262 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Grip Length:</b>	0.126 Inches Minimum And 0.187 Inches Maximum
<b>Shear Strength:</b>	1090 Single Pounds Per Square Inch
<b>Material:</b>	Iron Alloy 660 Overall
<b>Material Document And Classification:</b>	Ams 5737 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Body And Cadmium Body
<b>Surface Treatment:</b>	Passivate Locking Ring
<b>Surface Treatment:</b>	Passivate Sleeve
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec 1st Treatment Response Body Or Qq-p-416,type li,class 3 Fed Spec 2nd Treatment Response Body
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec 3rd Treatment Response Sleeve
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec 4th Treatment Response Locking Ring

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MLSP-EU04-03> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.