

Description

Fastener Length: 17/32"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---------------------------------------------|
| SKU / Model: | MLSPEU0606 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5320-00-227-1703 |
| Schedule B: | 7318.23.0000 |
| ECCN: | EAR99 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MLSP-EU06-06 Specifications

| | |
|-------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Fastener Length: | 0.537 Inches Maximum |
| Head Style: | Undercut Pan No. 2 |
| Head Height: | 0.080 Inches Minimum And 0.090 Inches Maximum |
| Shank Diameter: | 0.186 Inches Minimum And 0.190 Inches Maximum |
| Shank Style: | Self-plugging Mechanically Locked Stem |
| Head Major Diameter: | 0.356 Inches Minimum And 0.394 Inches Maximum |
| Expansion Device: | Serrated Stem-type W |
| Grip Length: | 0.313 Inches Minimum And 0.375 Inches Maximum |
| Material: | Iron Alloy 660 Locking Ring |
| Material: | Iron Alloy 660 Sleeve |
| Material: | Iron Alloy 660 Stem |
| Material Document And Classification: | Ams 5737 Assn Std Single Material Response Locking Ring |
| Material Document And Classification: | Ams 5737 Assn Std Single Material Response Stem |
| Material Document And Classification: | Ams 5737 Assn Std Single Material Response Sleeve |
| Surface Treatment: | Passivate Locking Ring |
| Surface Treatment: | Passivate Sleeve Or Cadmium Sleeve And Chromate Sleeve Or Aluminum Alloy Sleeve |
| Surface Treatment: | Passivate Stem |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec 1st Treatment Response Sleeve Or Qq-p-416,ty 2,cl 3 Fed Spec 2nd Treatment Response Sleeve Or Nas 4006 Assn Std 3rd Treatment Response Sleeve |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Locking Ring |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Stem |
| Specification/standard Data: | 80205-nas1919 Professional/Industrial Association Standard |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MLSP-EU06-06> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.