

Description

Fastener Length: 17/32"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

|                         |   |
|-------------------------|---|
| SKU / Model:            | MLSPEU0606                                  |
| Minimum Qty (MOQ):      | 5 EA  |
| NSN:                    | 5320-00-227-1703                            |
| Schedule B:             | 7318.23.0000                                |
| ECCN:                   | EAR99                                       |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |



\* See page 2 for technical characteristics

## P/N MLSP-EU06-06 Specifications

|   |  |
|---|--|
| <b>Fastener Length:</b>                               | 0.537 Inches Maximum   |
| <b>Head Style:</b>                                    | Undercut Pan No. 2   |
| <b>Head Height:</b>                                   | 0.080 Inches Minimum And 0.090 Inches Maximum  |
| <b>Shank Diameter:</b>                                | 0.186 Inches Minimum And 0.190 Inches Maximum  |
| <b>Shank Style:</b>                                   | Self-plugging Mechanically Locked Stem   |
| <b>Head Major Diameter:</b>                           | 0.356 Inches Minimum And 0.394 Inches Maximum  |
| <b>Expansion Device:</b>                              | Serrated Stem-type W   |
| <b>Grip Length:</b>                                   | 0.313 Inches Minimum And 0.375 Inches Maximum  |
| <b>Material:</b>                                      | Iron Alloy 660 Locking Ring  |
| <b>Material:</b>                                      | Iron Alloy 660 Sleeve  |
| <b>Material:</b>                                      | Iron Alloy 660 Stem  |
| <b>Material Document And Classification:</b>          | Ams 5737 Assn Std Single Material Response Locking Ring  |
| <b>Material Document And Classification:</b>          | Ams 5737 Assn Std Single Material Response Stem  |
| <b>Material Document And Classification:</b>          | Ams 5737 Assn Std Single Material Response Sleeve  |
| <b>Surface Treatment:</b>                             | Passivate Locking Ring   |
| <b>Surface Treatment:</b>                             | Passivate Sleeve Or Cadmium Sleeve And Chromate Sleeve Or Aluminum Alloy Sleeve  |
| <b>Surface Treatment:</b>                             | Passivate Stem   |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-35 Fed Spec 1st Treatment Response Sleeve Or Qq-p-416,ty 2,cl 3 Fed Spec 2nd Treatment Response Sleeve Or Nas 4006 Assn Std 3rd Treatment Response Sleeve |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-35 Fed Spec Single Treatment Response Locking Ring  |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-35 Fed Spec Single Treatment Response Stem  |
| <b>Specification/standard Data:</b>                   | 80205-nas1919 Professional/industrial Association Standard   |

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MLSP-EU06-06> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.