

**Description**

Fastener Length: 11/32"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MLSPM0404
Minimum Qty (MOQ):	10 EA
NSN:	5320-00-945-8430
Schedule B:	7508.90.5000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N MLSP-M04-04 Specifications

<b>Fastener Length:</b>	0.345 Inches Minimum And 0.365 Inches Maximum
<b>Head Style:</b>	Universal
<b>Head Height:</b>	0.054 Inches Minimum And 0.064 Inches Maximum
<b>Shank Diameter:</b>	0.124 Inches Minimum And 0.128 Inches Maximum
<b>Shank Style:</b>	Self-plugging Mechanically Locked Stem
<b>Head Major Diameter:</b>	0.238 Inches Minimum And 0.262 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Grip Length:</b>	0.188 Inches Minimum And 0.250 Inches Maximum
<b>Shear Strength:</b>	1020 Single Pounds Per Square Inch
<b>Material:</b>	Nickel Alloy 400 Stem
<b>Material:</b>	Steel Comp 630 Sleeve
<b>Material Document And Classification:</b>	Ams 5643 Assn Std Single Material Response Sleeve

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MLSP-M04-04> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.