

Description

Fastener Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|--|
| SKU / Model: | MLSPM0404C |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5320-00-390-0760 |
| Schedule B: | 7508.90.5000 |
| ECCN: | EAR99 |
| National Motor Freight: | 139820, Nickel Bolts / Nails / Nuts / Rivets Etc |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MLSP-M04-04C Specifications

| | |
|---|--|
| Fastener Length: | 0.385 Inches Maximum |
| Head Style: | Universal |
| Head Height: | 0.054 Inches Minimum And 0.064 Inches Maximum |
| Shank Diameter: | 0.124 Inches Minimum And 0.128 Inches Maximum |
| Shank Style: | Self-plugging Mechanically Locked Stem |
| Head Major Diameter: | 0.238 Inches Minimum And 0.262 Inches Maximum |
| Expansion Device: | Serrated Stem-type W |
| Grip Length: | 0.188 Inches Minimum And 0.250 Inches Maximum |
| Special Features: | Self Locking |
| Material: | Iron Alloy 660 Stem |
| Material: | Nickel Alloy 400 Sleeve Or Nickel Alloy R-405 Sleeve |
| Material Document And Classification: | Ams 5737 Assn Std Single Material Response Stem |
| Material Document And Classification: | Qq-n-281 Fed Spec All Material Responses Sleeve |
| Surface Treatment: | Cadmium Sleeve And Chromate Sleeve Or Aluminum Alloy Sleeve |
| Surface Treatment: | Passivate Stem |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Stem |
| Surface Treatment Document And Classification: | Qq-p-416 Ty 2 Cl 3 Fed Spec 1st Treatment Response Sleeve Or Nas 4006 Assn Std 2nd Treatment Response Sleeve |
| Specification/standard Data: | 80205-nas1919 Professional/industrial Association Standard |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MLSP-M04-04C> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.