

P/N MS14101-16K

Description

MS14101 series bearing

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

| SKU / Model: | MS1410116K |
|-------------------------|-------------------------------|
| Minimum Qty (MOQ): | 1 |
| NSN: | 3120-01-320-2026 |
| National Motor Freight: | 114800, Bearing,roller,thrust |



^{*} See page 2 for technical characteristics

P/N MS14101-16K Specifications

| Bore Diameter: | 0.9995 Inches Minimum And 1.0000 Inches Maximum |
|---------------------------------------|---|
| Outer Member Outside Diameter: | 1.7495 Inches Minimum And 1.7500 Inches Maximum |
| Outer Member Width: | 0.7920 Inches Minimum And 0.8020 Inches Maximum |
| Inner Member Width: | 0.9980 Inches Minimum And 1.0000 Inches Maximum |
| Static Radial Load Rating: | 82200 Pounds |
| Hardness Rating: | 28.0 Rockwell C Minimum Outer Race Member And 37.0 Rockwell C Maximum Outer Race Member |
| Hardness Rating: | 55.0 Rockwell C Minimum Inner Member And 62.0 Rockwell C Maximum Inner Member |
| Lubrication Feature: | Self-lubricating Liner Race Liner |
| Material: | Plastic Polytetrafluoroethylene Race Liner |
| Material: | Steel Comp 440c Inner Member |
| Material: | Steel Comp 630 Outer Race Member |
| Material Document And Classification: | Ams 5630 Assn Std 1st Material Response Inner Member |
| Material Document And Classification: | Ams 5643 Assn Std Single Material Response Outer Race Member |
| Style Designator: | With Insert And/or Liner With Staking Groove |

How to Order

Order this plain self-aligning bearing from our inventory online by visiting https://military-fasteners.com/bearings/plain+self_aligning+bearings/MS14101-16K and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.