

# P/N MS14101-3

## **Description**

inner diameter: 3/16" outer diameter: 9/16", self-lubricating, self aligning, low speed, narrow, grooved outer ring, MS14101 series bearing

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

### **Additional Information**

#### **Alternate Part Numbers**

03-825-03

SKU / Model:	MS141013
Minimum Qty (MOQ):	1
NSN:	3120-01-130-9145
Schedule B:	8483.30.8070
ECCN:	EAR99
National Motor Freight:	114820, Bearings / Bushings Noi Ball / Roller









# P/N MS14101-3 Specifications

Bore Diameter:	0.1895 Inches Minimum And 0.1900 Inches Maximum
Outer Member Outside Diameter:	0.5620 Inches Minimum And 0.5625 Inches Maximum
Outer Member Width:	0.2130 Inches Minimum And 0.2230 Inches Maximum
Inner Member Width:	0.2790 Inches Minimum And 0.2810 Inches Maximum
Static Radial Load Rating:	3975 Pounds
Special Features:	Passivation Optional

### **How to Order**

Order this plain self-aligning bearing from our inventory online by visiting <a href="https://military-fasteners.com/bearings/plain+self\_aligning+bearings/MS14101-3">https://military-fasteners.com/bearings/plain+self\_aligning+bearings/MS14101-3</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.