

Description

inner diameter: 3/16" outer diameter: 9/16", self-lubricating, self aligning, low speed, narrow, grooved outer ring, MS14101 series bearing

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[03-825-03](#)

| | |
|-------------------------|-----------------------------------------------|
| SKU / Model: | MS141013 |
| Minimum Qty (MOQ): | 1 |
| NSN: | 3120-01-130-9145 |
| Schedule B: | 8483.30.8070 |
| ECCN: | EAR99 |
| National Motor Freight: | 114820, Bearings / Bushings Noi Ball / Roller |



P/N MS14101-3 Specifications

| | |
|---------------------------------------|-------------------------------------------------|
| Bore Diameter: | 0.1895 Inches Minimum And 0.1900 Inches Maximum |
| Outer Member Outside Diameter: | 0.5620 Inches Minimum And 0.5625 Inches Maximum |
| Outer Member Width: | 0.2130 Inches Minimum And 0.2230 Inches Maximum |
| Inner Member Width: | 0.2790 Inches Minimum And 0.2810 Inches Maximum |
| Static Radial Load Rating: | 3975 Pounds |
| Special Features: | Passivation Optional |

How to Order

Order this plain self-aligning bearing from our inventory online by visiting https://military-fasteners.com/bearings/plain+self_aligning+bearings/MS14101-3 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.