

Description

single row, self lubricating

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|--------------------|------------------|
| SKU / Model: | MS141013P |
| Minimum Qty (MOQ): | 2 |
| NSN: | 3120-01-520-6277 |
| ECCN: | 9A991 |



* See page 2 for technical characteristics

P/N MS14101-3P Specifications

| | |
|---------------------------------------|---|
| Bore Diameter: | 0.1895 Inches Minimum And 0.1900 Inches Maximum |
| Outer Member Outside Diameter: | 0.5620 Inches Minimum And 0.5625 Inches Maximum |
| Outer Member Width: | 0.2130 Inches Minimum And 0.2230 Inches Maximum |
| Inner Member Width: | 0.2790 Inches Minimum And 0.2810 Inches Maximum |
| Hardness Rating: | 28.0 Rockwell C Minimum Outer Race Member And 37.0 Rockwell C Maximum Outer Race Member |
| Hardness Rating: | 55.0 Rockwell C Minimum Inner Member And 62.0 Rockwell C Maximum Inner Member |
| Lubrication Feature: | Self-lubricating Liner Race Liner |
| Material: | Steel Comp 440c Inner Member And Steel Comp 630 Inner Member |
| Surface Treatment: | Cadmium Outer Race Member And Chromate Outer Race Member |
| Style Designator: | With Insert And/or Liner With Staking Groove |

How to Order

Order this plain self-aligning bearing from our inventory online by visiting https://military-fasteners.com/bearings/plain+self_aligning+bearings/MS14101-3P and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.