

Description

single row, self lubricating

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS141013P
Minimum Qty (MOQ):	2
NSN:	3120-01-520-6277
ECCN:	9A991



* See page 2 for technical characteristics

P/N MS14101-3P Specifications

Bore Diameter:	0.1895 Inches Minimum And 0.1900 Inches Maximum
Outer Member Outside Diameter:	0.5620 Inches Minimum And 0.5625 Inches Maximum
Outer Member Width:	0.2130 Inches Minimum And 0.2230 Inches Maximum
Inner Member Width:	0.2790 Inches Minimum And 0.2810 Inches Maximum
Hardness Rating:	28.0 Rockwell C Minimum Outer Race Member And 37.0 Rockwell C Maximum Outer Race Member
Hardness Rating:	55.0 Rockwell C Minimum Inner Member And 62.0 Rockwell C Maximum Inner Member
Lubrication Feature:	Self-lubricating Liner Race Liner
Material:	Steel Comp 440c Inner Member And Steel Comp 630 Inner Member
Surface Treatment:	Cadmium Outer Race Member And Chromate Outer Race Member
Style Designator:	With Insert And/or Liner With Staking Groove

How to Order

Order this plain self-aligning bearing from our inventory online by visiting https://military-fasteners.com/bearings/plain+self_aligning+bearings/MS14101-3P and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.