

## Description

single row, self lubricating

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	MS141013P
Minimum Qty (MOQ):	2
NSN:	3120-01-520-6277
ECCN:	9A991



\* See page 2 for technical characteristics

## P/N MS14101-3P Specifications

<b>Bore Diameter:</b>	0.1895 Inches Minimum And 0.1900 Inches Maximum
<b>Outer Member Outside Diameter:</b>	0.5620 Inches Minimum And 0.5625 Inches Maximum
<b>Outer Member Width:</b>	0.2130 Inches Minimum And 0.2230 Inches Maximum
<b>Inner Member Width:</b>	0.2790 Inches Minimum And 0.2810 Inches Maximum
<b>Hardness Rating:</b>	28.0 Rockwell C Minimum Outer Race Member And 37.0 Rockwell C Maximum Outer Race Member
<b>Hardness Rating:</b>	55.0 Rockwell C Minimum Inner Member And 62.0 Rockwell C Maximum Inner Member
<b>Lubrication Feature:</b>	Self-lubricating Liner Race Liner
<b>Material:</b>	Steel Comp 440c Inner Member And Steel Comp 630 Inner Member
<b>Surface Treatment:</b>	Cadmium Outer Race Member And Chromate Outer Race Member
<b>Style Designator:</b>	With Insert And/or Liner With Staking Groove

## How to Order

Order this plain self-aligning bearing from our inventory online by visiting [https://military-fasteners.com/bearings/plain+self\\_aligning+bearings/MS14101-3P](https://military-fasteners.com/bearings/plain+self_aligning+bearings/MS14101-3P) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.